



NOTES

1. WORKING FLUIDS : OIL
2. WORKING TEMPERATURE : -50°C~120°C
3. WORKING PRESSURE : 45 psi
4. SURFACE TREATMENT : ANSI 70 / GRAY

11	PACKING	1	HNBR		BK-BF100-A08
10	O-RING	1	HNBR	G30	
9	Stainless Steel Lock Washer	2	SUS304	M8용	
8	Stainless Steel Hex Head Cap Screw	2	SUS304	M8x25L	
7	PACKING	1	HNBR ,VITON		BK-BF80-A07
6	Brass Washer	2	C3604		BK-BF80-A06
5	Blass Gland Nut	1	C3604		BK-BF80-A05
4	Operating Handle	1	SS400	FORGING	BK-BF100-Y04
3	Operating Shaft	1	S45C	FORGING	BK-BF100-Y03
2	Operating Disk	1	ALDC8S	DIECASTING	BK-BF100-A02
1	Valve Body	1	FC20	CASTING	BK-BF100-Y01

NO	PART NAME	Q'TY	MATERIAL	DIMENSION	REMARK
MATERIAL		DIMENSION		WEIGHT	
REF No.					REV.
DWG. NO. BK-BF100-Y00					NO. 1

TITLE
4" FLANGE TYPE BUTTERFLY VALVE

△	2008.02.04	NAME PLATE replaced , SHAFT length changed	T.K.HEO
REV.	DATE	CONTENTS	DSN'D BY

SCALE	DSN'D BY	CHK'D BY	CHK'D BY	APP'D BY
N/S	T.K.HEO 2007.11.23	H.J.JU 2007.11.23	S.H.AHN 2007.11.23	J.G.BAE 2007.11.23
BTX CO., LTD.				